



1.CONSTRUCTION

RATED VOLTAGE	62930 IEC131/ H1Z2Z2-K 6mm ²		REVISION:	A/0	FORM NO.	B274
	DC1500V		CONSTRUCTION D.W.G			
Conductor	Cross-sectional Area	6mm ²	 			
	Material	Stranded Tinned Copper				
	Conductor.Size (mm)	84/0.285				
	Approx. Stranded OD.(mm)	2.96				
Inner Layer	Material	XLPO				
	AVG Thickness (mm)	0.70				
	Min Thickness (mm)	0.53				
	OD.(mm)	4.45±0.10				
Outer Layer	Material	XLPO				
	AVG Thickness (mm)	0.80				
	Min Thickness (mm)	0.58				
	OD. (mm)	6.10±0.15				
	Color	Black	INNER AND OUTER LAYER IS INSEPARABLE .			

2.MECHANICAL CHARACTERISTICS

ITEM	SPECIFICATION		
		INNER LAYER	OUTER LAYER
Elongation	Un-aged	≥125%	≥125%
Strength		≥8MPa	≥8MPa
Cold bend test	(-40 ± 2.0°C × 16h)	No cracking	
Flame test	IEC60332-1-2	PASS	
Rated temperature	-40°C up to +90°C		
Thermal endurance properties	Elongation≥50% Temperature index≥120		

3.ELECTRICAL CHARACTERISTICS

ITEM	SPECIFICATION
Max. Conductor DC Resistance at 20°C	≤3.39Ω/km
Dielectric Strength	6.5kV/5min
Spark test	10000VAC
Insulation resistance at 20°C	≥610MΩ·km
Max. current at 30°C	72A

4.STANDARD

PRODUCT STANDARD CERTIFICATION	Reference Standard:
R50477532&R50477533	EN50618&IEC62930

5.MARKING

SK-R ▲ TÜV 62930 IEC131/H1Z2Z2-K 6mm² IEC62930/EN50618 Dca AD7 DC1500V -40°C HALOGEN FREE LOW SMOKE SUNKEAN CABLE CE *

NOTE:* Represent meter marking, Meter marking like 0, 1, 2 until 99999.

6.PACKING

- (a) 250m、500m、1000m
- (b) Consulting if delivering in other ways

Part No.	Serial No.	Drawing	Checked	Approved	Date	APPROVED
PVG-T01600-24301	002	Zoey	Max	Defree	2025/4/1	